

STREAM CLOSED COUPLED PAN

FITTING INSTRUCTIONS

Please retain for future reference

IMPORTANT - Read before installation

- Before fitting ensure that there is no damage to the product and there are no missing parts.
- We strongly recommend the use of a qualified plumber throughout the installation.
- Flush out all impurities and debris from pipe work prior to installation
- Fix all outlet and inlet valves before installation.
- Periodic cleaning and maintenance should be used to avoid formation of damaging lime scale deposits. Aggressive cleaning agents may damage some materials such as the seat hinges and other plastic components. Only clean with warm soapy water.
- Do not introduce caustic chemical substances into the cistern. These can damage the valve components and cause product failure.

INSTALLATION INSTRUCTIONS

1. Position the floor fittings, flush pipe from the concealed cistern and the soil pipe as shown in diagram A. Also make provision for the inlet feed.
2. Install the fittings in the cistern using the instructions supplied. Fit the cistern to the pan ensuring that the gasket is fitted between the cistern and pan around the base of the flush valve.
3. Use the fixing hardware supplied with the flush fittings to secure the tank in place. Do not overtighten the fittings as this could damage the ceramic.
4. Connect the cistern to the water inlet using a flexible hose before pushing the pan back in place (Diagram B).
5. Check that the soil pipe and water inlets are properly connected before flush testing the pan and checking for any leaks.
6. Connect the pan floor fittings as shown in Diagram C.

